



DATA SHEET

Hall Effect Current Sensor

PN: CHB_LSP3S1

IPN=05~25A

Feature

- Closed- loop (compensated) current transducer
- Capable measurement of currents: DC, AC, pulse with galvanic isolation between primary circuit and secondary circuit.
- Supply voltage: DC +3.3V
- PCB mounting installation

Advantages

- High accuracy
- Low temperature drift
- Optimized response time, no insertion losses
- Low power consumption
- Very good linearity
- Can be customized

Applications

- Photovoltaic (PV) current applications
- AC/DC variable-speed drive
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Inverter applications



RoHS

Electrical data: (Ta=25°C, Vc=+3.3VDC, RL=2KΩ, CL=10000pF)

Parmeter \ Ref	CHB05LSP3S1	CHB10LSP3S1	CH20LSP3S1	CHB25LSP3S1
Rated input I _{pn} (A)	05	10	20	25
Measuring range I _p (A)	0~±05	0~±10	0~±20	0~±25
Turns ratio N _p /N _s (T)	1:800	1:800	1:800	1:1000
Inside resistance R _M (Ω)	200±0.1%	100±0.1%	50±0.1%	25±0.1%
Output voltage V _o (V)	1.650±1.250*(IP/IPN)			
Output voltage V _o (V)	@IP=0, T=25°C		1.650	
Supply voltage V _C (V)	+3.3 ±5%			
Accuracy X _G (%)	@IPN, T=25°C		< ±0.7	
Offset voltage V _{OE} (mV)	@IP=0, T=25°C		< ±20	
Temperature variation of V _{OE} V _{OT} (mV/°C)	@IP=0, -40 ~ +85°C		< ±0.5	
Linearity error e _r (%FS)	< 0.1			
Di/dt accurately followed (A/μs)	> 50			
Response time t _{ra} (μs)	@90% of IPN		< 1.0	
Power consumption I _C (mA)	10+I _s			
Bandwidth BW(KHZ)	@-3dB, IPN		DC-200	



Insulation voltage Vd(KV)	@50/60Hz, 1min,AC	4.0
---------------------------	-------------------	-----

General data:

Parameter	Value
Operating temperature TA(°C)	-40 ~ +85
Storage temperature TS(°C)	-55~ +125
Mass M(g)	10
Plastic material	PBT G30/G15, UL94- V0;
Standards	IEC60950-1:2001
	EN50178:1998
	SJ20790-2000

Dimensions(mm):

	<p>Connection</p>
	<p>General tolerance</p> <p>General tolerance: <math>\pm 0.2\text{mm}</math> Primary through-hole: $D8.5 \pm 0.15\text{mm}$ Fixed pin: $0.8 \times 0.9 \pm 0.15\text{mm}$; Secondary pin: 3pin 0.25×0.5</p>

Remarks:

- When the current goes through the primary pin of a sensor, the voltage will be measured at the output end.
- Custom design is available for the different rated input current and the output voltage.
- The dynamic performance is the best when the primary hole is fully filled with.
- The primary conductor should be $<100^\circ\text{C}$.

WARNING : Incorrect wiring may cause damage to the sensor.

