



DATA SHEET

Hall Effect Current Sensor

PN: CHK_HB15D4

IPN=2000-10000A

Feature

- Open- loop
- Capable measurement of currents: DC, AC, pulse with galvanic isolation between primary circuit and secondary circuit.
- Supply voltage: DC $\pm 12 \sim 15V$

Advantages

- High accuracy
- Easy installation
- No insertion losses
- Low power consumption
- Wide current measuring range
- High immunity to external interference
- Very good linearity
- Can be customized



Applications

- Inverter applications
- AC/DC variable-speed drive
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Frequency drive control home appliances



RoHS



Electrical data: ($T_a=25^\circ C$, $V_c=\pm 15VDC$, $R_L=10K\Omega$)

| Parameter \ Ref | CHK2000 HB15D4 | CHK3000 HB15D4 | CHK4000 HB15D4 | CHK6000 HB15D4 | CHK8000 HB15D4 | CHK10000 HB15D4 |
|--|--------------------------------|---------------------|---------------------|----------------------|----------------------|----------------------|
| Rated input $I_{pn}(A)$ | 2000 | 3000 | 4000 | 6000 | 8000 | 10000 |
| Measuring range $I_p(A)$ | 0 \sim ± 4000 | 0 \sim ± 6000 | 0 \sim ± 8000 | 0 \sim ± 12000 | 0 \sim ± 12000 | 0 \sim ± 12000 |
| Output voltage $V_o(V)$ | $\pm 4.0 * (I_p / I_{PN})$ | | | | | |
| Load resistance $R_L(K\Omega)$ | > 10 | | | | | |
| Supply voltage $V_C(V)$ | $(\pm 12 \sim \pm 15) \pm 5\%$ | | | | | |
| Accuracy $X_G(\%)$ | @IPN, $T=25^\circ C$ | | $< \pm 1.0$ | | | |
| Offset voltage $VOE(mV)$ | @IP=0, $T=25^\circ C$ | | $< \pm 25$ | | | |
| Temperature variation of VOE $VOT(mV/^\circ C)$ | @IP=0, $-40 \sim +85^\circ C$ | | $< \pm 1.0$ | | | |
| Hysteresis offset voltage VOH(mV) | @IP=0, after 1*IPN | | $< \pm 25$ | | | |
| Linearity error $\epsilon_r(\%FS)$ | < 1.0 | | | | | |
| Di/dt accurately followed (A/ μs) | > 100 | | | | | |
| Response time $t_{ra}(\mu s)$ | @90% of IPN | | < 7.0 | | | |
| Power consumption $I_C(mA)$ | 15 | | | | | |



Cheemi Technology Co., Ltd

| | | |
|---------------------------|-------------------|-------|
| Bandwidth Bw(KHZ) | @-3dB, IPN | DC-20 |
| Insulation voltage Vd(KV) | @50/60Hz, 1min,AC | 6.0 |

General data:

| Parameter | Value |
|------------------------------|------------------------|
| Operating temperature TA(°C) | -40 ~ +85 |
| Storage temperature TS(°C) | -55 ~ +125 |
| Mass M(g) | 1150 |
| Plastic material | PBT G30/G15, UL94- V0; |
| Standards | IEC60950-1:2001 |
| | EN50178:1998 |
| | SJ20790-2000 |

Dimensions(mm):

| | |
|--|---|
| | <p style="text-align: center;">Connection</p> |
| | <p style="text-align: center;">General tolerance</p> <p>General tolerance: <math>\pm 0.5\text{mm}</math> Primary through-hole : $50*140\pm 0.3$ Connection of Secondary : DG303-5.0-04P</p> |

Remarks:

- When the current goes through the primary pin of a sensor, the voltage will be measured at the output end.
- Custom design is available for the different rated input current and the output voltage.
- The dynamic performance is the best when the primary hole is fully filled with.
- The primary conductor should be <math>< 100^{\circ}\text{C}</math>.

WARNING : Incorrect wiring may cause damage to the sensor.

