


## Order No.:

CJUD10-12M-NAH
CJUD10-12M-NBH
CJUD10-12M-PAH
CJUD10-12M-PBH
CJUD10-12M-DAH
CJUD10-12M-DBH

## Features

- Special optical design on the product's back cover, providing 360° visible indicator lights.
- Dedicated IC, stable ultra-long detection distance, and strong anti-interference capabilities.
- Uses durable, oil-resistant cables.
- Detection surface made of oil-resistant, corrosion-resistant material, offering strong environmental resistance.


## Wiring




## Accessory

Serrated Flange Nuts *2

## Overall dimension




## Technical Parameters

| | |
|---|---|
| **General description** | |
| Switch point function | NPN 、PNP、D |
| Rated operating distance Sn | 10mm |
| Installation | Non-Flush mounting |
| Standard detector | 24*24*1t(Q253A) |
| Reliable operating distance Sa | 0...8mm |
| **Rated grade** | |
| Rated voltage UB | DC10...30V(Including fluctuation (p-p) 10% |
| Switching frequency f | 0.5KHz |
| Hysteresis range | ≤ 15% of sensing distance |
| Repeatability | <3% of detection distance |
| No load current Io | <12mA |
| Voltage drop Ud | NPN/PNP:<2V； DC two-wire<3V |
| Working current IL | ＜200mA |
| Leakage current | ＜100uA |
| Circuit protection | Reverse polarity protection, short-circuit protection |
| Switching state indication | Red LED indicator |
| **Surrounding environment** | |
| Ambient temperature | -25℃...70℃ (No icing,no condensation) |
| Temperature effect | -Within 25 ℃... 70 ℃, within 15% of detection distance at+24 ℃ |
| Ambient humidity | 35...95%RH (No condensation) |
| Influence of voltage | <3% |
| **Mechanical properties** | |
| Wiring | 2m standard cable |
| Shell material | Brass plated with pearl nickel |
| Sensing surface | PBT |
| Protection level | IP67 |
| Withstand Voltage | AC 500V , 50/60Hz 1 minute between the whole charging part and the shell |
| Insulation resistance | ≥20 MΩ (DC 500 V with a megohmmeter) between the whole charging part and the shell |
| Vibration resistance | 10～55 Hz, complex amplitude 1.5mm, 2H in X, Y and Z directions |
| **Certification and Standards** | |
| Product certification | CE CCC CQC ISO9001 ISO14001 ISO45001 |
| Unit weight | About 25g |

The datasheet is subject to change without notice. Copyright Cheemi Tech