



DATA SHEET

Hall Effect Current Sensor

PN: CHK_EKADA24S0/4

IPN=50-600A

Feature

- Open- loop current transducer using the hall effect
- Capable measurement of currents: DC, AC,pulse with galvanic isolation between primary circuit and secondary circuit.
- Output signal can be directly acquisition-ed by the PLC or DSP terminal control system.
- Supply voltage: DC +12.0~+24.0V

Advantages

- Easy installation
- No insertion losses
- Low power consumption
- Wide current measuring range
- High immunity to external interference
- Can be customized

Applications

- The application of variable frequency electrical appliances
- AC/DC variable-speed drive
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Inverter applications



Electrical data: (Ta=25°C, Vc=+24.0VDC)

Parmeter	Ref	CHK50EK ADA24S4	CHK100E KADA24S 4	CHK200E KADA24S 4	CHK300E KADA24S 4	CHK400E KADA24S 4	CHK600E KADA24S 4
Rated input Ipn(A)		50	100	200	300	400	600
Measuring range Ip(A)		0 ~ +100	0 ~ +200	0 ~ +400	0 ~ +600	0 ~ +800	0 ~ +1200
Output current Io(mA)		@CHK-EKADA24S4 4.0+16.0*(IP/IPN),DC					
Output current Io(mA)		@IP=0,CHK-EKADA24S4 4.0±0.15,DC					
Output current Io(mA)		@CHK-EKADA24S0 +20.0*(IP/IPN),DC					
Offset current IOE(mA)		@IP=0,CHK-EKADA24S0 < +0.2					
Supply voltage VC(V)		(+12.0~+24.0) ±5%					
Accuracy XG(%)		@IPN,T=25°C < ±1.0					
Temperature variation of IOE IOT(mA/°C)		@IP=0,-40 ~ +85°C < ±0.005					
Linearity error er(%FS)		< 1.0					
Response time tra(ms)		@90% of IPN <20					
Power consumption IC(mA)		15+IO					



Cheemi Technology Co., Ltd

Bandwidth Bw(KHZ)	@-3dB,IPN	DC-2.0
Insulation voltage Vd(KV)	@50/60Hz, 1min,AC	2.5

General data:

Parameter	Value
Operating temperature TA(°C)	-40 ~ +85
Storage temperature TS(°C)	-55 ~ +125
Mass M(g)	70
Plastic material	PBT G30/G15, UL94- V0;
Standards	IEC60950-1:2001
	EN50178:1998
	SJ20790-2000

Dimensions(mm):

CHK-EKADA24S4M	CHK-EKADA24S4S	Connection
		<p>General tolerance</p> <p>General tolerance: <math>\pm 0.5\text{mm}</math></p> <p>Primary through-hole : <math>D21.0 \pm 0.3</math></p> <p>Connection of Secondary :</p> <p>CHK-EKADA24S4M: 2510-04A (Instead of Molex 5045-04A)</p> <p>CHK-EKADA24S4S: 15EDGK3.81-04P</p>

Remarks:

- When the current goes through the primary pin of a sensor, the voltage will be measured at the output end.
- Custom design is available for the different rated input current and the output voltage.
- The dynamic performance is the best when the primary hole is fully filled with.
- The primary conductor should be <math>< 100^\circ\text{C}</math>.

WARNING : Incorrect wiring may cause damage to the sensor.



Cheemi Technology Co., Ltd
 Tel: 025-85996365 E-mail: info@cheemi-tech.com www.cheemi-tech.com
 Add: N22, Xianlongwan, Xianyin South Road, Qixia District, Nanjing - China.